model 30112S

BOOM TRUCK

features

- 30 Ton (27,2 mton) Capacity
- 4-Section 112' (34,1 m) Proportional Boom
- 2-Section 26' (7,9 m) to 46' (14,0 m) Telescopic Jib
- 168' (51,3 m) Maximum Tip Height with Telescopic Jib
- 122' (37,2 m) Maximum Main Boom Tip Height
- Self-Lubricating Boom Slider Pads For Smooth Boom Extension
- Two Speed Planetary Grooved Drum Hoist With Negative Draft Flange
- Ride Around Operator Control Station
- Pilot Operated Crane Controls
- System Pressure Gauge
- Fully Enclosed Heated Cab Option
- Air Conditioner Option
- Continuous Rotation
- 360º Work Area
- Radio Remote Outrigger Controls with Audible Outrigger Motion Alarm
- Retracted, Intermediate And Fully Extended Outrigger Load Charts
- Load Moment Indicator with Digital Display, CANBus, Overload Shutdown and Internal Boom Length Cable
- Radio ATB
- Rugged, Weatherproof Electrical System with Circuit Status LEDs
- Removable Boom Rest
- Clamp-On Mounting
- Hydraulic Oil Cooler
- ORS Face Seal Hydraulic Fittings and Adapters
- Manitex ***UPTime*** Comprehensive Support



3000 South Austin Ave.
Georgetown, TX 78626-7544
T: 512-942-3000 F: 512-863-3776
www.manitex.com

Product Specification Sheet